

Funny Bike “RR FB EDRS Technical Rules for 2013”

Title

RR 1.1.1 Engine
RR 1.1.2 Frame
RR 1.1.3 Tires
RR 1.1.4 Body
RR 1.1.5 Wheelie Bars
RR 2.1 Reservations for Sweden:

For general construction rules and protective clothing and helmets we refer to UEM Technical Rules for Drag Bike 2013 at <http://www.uem-moto.eu> with local reservations.

RR 1.1 SPECIAL REGULATIONS FOR FUNNY BIKE

Reserved for single engine, alcohol, gasoline or nitro burning engines. 295 kg minimum weight including rider, forced induced nitro is not allowed. All bikes must have rear fender.

RR 1.1.1 Engine

Stock cases permitted; aftermarket cases are highly recommended.

Engine displacement:

Maximum 3278cc naturally aspirated, petrol, methanol or nitro

Maximum 2500cc with Nitrous Oxide, turbo or supercharger, petrol or methanol only.

RR 1.1.2 Frame

Wheelbase minimum is 1700 mm. Stock chassis prohibited. Minimum seat height (with rider in position and seat compressed) measured from lowest point of seating position to ground, 400 mm.

RR 1.1.3 Tires

Minimum rear tire size width is 10-inches. Maximum tire width is 14-inches.

RR 1.1.4 Body

All Funny Bikes rear fender must extend past the rear axle. Seats must have fabric or anti-skid texture. Front fairings must have transparent windscreens.

RR 1.1.5 Wheelie Bars

Wheelie bars are mandatory

RR 2.1 Reservations for Sweden:

Spine protector mandatory.

Nitrous Oxide not allowed.